

# THERMODYNAMIC CONCEPTS ON EFFICIENCY

*by* Faradiba Faradiba

---

**Submission date:** 01-Feb-2021 01:31PM (UTC+0700)

**Submission ID:** 1498861296

**File name:** EN\_Paper\_Termodinamika.docx (45.11K)

**Word count:** 2955

**Character count:** 15765

# THERMODYNAMIC CONCEPTS ON EFFICIENCY OF AIRCRAFT ENGINES

Faradiba Faradiba<sup>1\*</sup>, Endah Yuniarti<sup>2</sup>

19

<sup>1</sup>Department of Physics Education, Universitas Kristen Indonesia,  
Jl. Mayjen Sutoyo No. 2, Cawang-Jakarta 13630, Indonesia

<sup>2</sup>Aviation Engineering Study Program, Universitas Marsekal Suryadharma,  
*e-mail:* [faradiba@uki.ac.id](mailto:faradiba@uki.ac.id)

## Abstract

Along with the development of engine technology to be able to produce maximum efficiency in aircraft jet engines, various modifications were made to the machine tools. Modifications are made by taking into account four main factors, namely: maximum power output, reduced engine weight, low fuel consumption and maximum aircraft payload. This research uses a meta-analysis method, namely the analysis of several research results in line with what has been done previously regarding the efficiency of aircraft jet engines. The thermodynamic concept related to the heat engine which implements the Brayton cycle that maximum efficiency can be done by reducing wasted heat energy and maximizing the work produced. From this concept, several attempts to maximize aircraft efficiency, such as modification of design changes that have a significant impact on weight reduction, fuel barrier design with low fan pressure, high bypass design ratio are also carried out in an effort to reduce aircraft noise levels. Aircraft noise levels can also be minimized by modifying the nozzle and ejector on the engine.

**Key words:** thermodynamics, jet engines, aircraft

## 1. INTRODUCTION

News of the Sriwijaya Air SJ-182 airplane crash on January 9, 2021, which has caused quite a lot of speculation. Some of them stated that the wrong cause of the accident occurred because the plane was 26 years old. based on the Decree of the Ministry of Transportation Number 115 of 2020 which states that "the age limit for aircraft that is registered and operated for the first time in Indonesia is provided that aircraft in the transportation category for passenger transportation are at most 20 years old" ([Keputusan Menteri Perhubungan Republik Indonesia Nomor KM 115 Tahun 2020, 2020](#)). Some aviation experts say that the age of an airplane is not a major factor in the occurrence of airplane accidents. One of the factors that can cause an aircraft to be unfit for flight apart from weather and crew performance is a technical factor. The technical factor referred to here is aircraft maintenance ([Priyono, 2020](#)). Aircraft engine maintenance includes the structure of the frame and engine

to the electrical system, radio installations and instrumentation. Machine maintenance is carried out regularly and non-routine (Kusmayanti, 2016).

The importance of maintenance on aircraft engines because several machine tools that are related to each other have quite sensitive characteristics. There are several machine tools which, if not carried out routine maintenance, can result in prolonged humidity which in turn can cause corrosion on the machine. Machines that are not used within 2-3 days, it is possible that the equipment in the machine has corroded. If one of the machine tools has a problem or cannot function optimally, it will have a direct impact on the function of the other equipment which results in the machine not working properly. (Rosyidin, 2017).

Based on thermodynamic principles regarding optimal work on an engine depending on engine performance. The lower the heat output produced, the more work a machine can produce. A jet engine is a machine that can power an airplane that applies the Brayton thermodynamic cycle. This jet engine, known as a gas turbine engine, requires high speed. Various modifications to the jet engine used in aircraft such as turbojet and turbofan engines, rocket engines, ramjets and pump jets.

A turbojet engine is a fairly simple type of jet engine. Not only used in aircraft, but this turbojet engine is used on ships. This machine is powerful 28000 hp with operations that require high speed (Seldner, 1972). Another type of jet engine that is commonly used is a turbofan engine. Turbofan engines are usually used in commercial aircraft and fighter aircraft. In this engine, some of the air is flowed into the combustion chamber, some of it is flowed outside the combustion chamber. In this engine, the air also simultaneously functions as a coolant (lowers the temperature) in the combustion chamber (Schwarz & Gorbounov, 2014). The next type of jet engine is a turboprop engine. This machine is a turbojet engine equipped with an additional turbine. Apart from being fuel efficient, this machine also has a low noise level. In contrast to a turboprop engine, a turboshaft engine is a type of jet engine, in contrast to a turboprop engine. In this machine is a turboprop engine without using additional turbines. Usually this machine is used on a helicopter (Aydın et al., 2013).

In general, a jet engine is a power-producing engine on an airplane. The components of this machine are the inlet, propulsion turbine, compressor, burner and nozzle. Jet engines have the basic principle of a combustion process that produces heat with high temperatures. As a result of this high temperature, it produces a very fast speed, in other words, from this process the jet engine provides / produces a large amount of energy / power. The advantages of a jet engine are that it produces enormous energy, can travel long distances and produces low vibrations. Of the advantages that a jet engine has, of course, there are drawbacks

including high fuel consumption, maintenance that requires high costs and also a high level of noise. (Royce, 2015).

In a jet engine work system in an airplane can be explained simply by simple thermodynamic concepts. Whereas in general the maximum efficiency in a heat engine can be generated by reducing the heat input and maximizing the incoming heat is converted into work with the smallest possible waste.

## 2. DATA AND METHODOLOGY

This research uses a meta-analysis research method. In this method, analysis of several research results is carried out in line with what has been done previously by raising similar problems. The data collection process was carried out using documentation techniques in the form of literature related to thermodynamic analysis on jet engines. Several types of literature are used such as articles in scientific journals and the like, both national and international, books related to jet engines and thermodynamic cycles and several published research results. The sampling technique used was purposive sampling technique which was deliberately selected so that the information generated was in accordance with the content of this research.

## 3. RESULTS AND DISCUSSION

The jet engine is an application of a heat engine whose simple scheme applies the second law of thermodynamics. Specifically, this jet engine has a cycle according to the Brayton cycle (Hermawan et al., 2018). This heat burning machine accelerates the mass of air and produces heat at high temperatures. So that it produces great energy.

The Brayton cycle, which is applied to a jet engine, consists of 4 stages of the thermodynamic process (Retnowati et al., 2019).

### 1. Isentropic Compression Process

In isentropic compression, air enters the gas turbine system through the compressor inlet. From the compressor, the air is compressed at a certain pressure followed by a narrowing of the volume of the combustion chamber. In this process the entropy in the system is considered constant (Muku & Sukadana, 2009). Based on a reversible process according to the first law of thermodynamics, work is generated in this process (Haryanto, 2016):

$$dQ = dW + dU \quad (1)$$

Where is the isentropic process  $dQ = 0$  AND  $U = nc_v(T_2 - T_1)$  :

$$dW = -dU$$

$$W_1 = - \int dU = - \int_{T_1}^{T_2} nc_v dT = nc_v(T_2 - T_1) \quad (2)$$

## 2. Isobaric combustion process

In the isobaric combustion process, compressed air enters the combustion chamber, the heat energy from the combustion is absorbed by the air, increasing the air temperature and increasing the air volume. In this process the pressure is constant because there is no pressure increase because the air from combustion is free from expansion to the side of the turbine (Muku & Sukadana, 2009). Work generated in this process:

$$W_2 = p (V_2 - V_1) \quad (3)$$

## 3. Isentropic expansion process

In this isentropic expansion process, where the compressed air from the combustion products expands through the turbine. Turbine blades which are small nozzles function to convert the hot energy of the air into kinetic energy in the form of propulsion of the aircraft by a large nozzle at the end of the turbine gas output. (Muku & Sukadana, 2009). Work generated in this process:

$$W_3 = - \int dU = - \int_{T_1}^{T_2} nc_v dT = -nc_v(T_1 - T_2) \quad (4)$$

In this case  $T_1 > T_2$

## 4. Isobaric heat dissipation process

Pada proses pembuangan panas, dimana udara dibuang ke atmosfer. Panas yang disap oleh udara bebas, sehingga siklus udara siap untuk kembali masuk ke tahap kompresi isentropic (Muku & Sukadana, 2009). Work generated in this process:

$$W_4 = p (V_2 - V_1) \quad (5)$$

Referring to the brayton cycle concept, the calculation of engine efficiency can be calculated. The total work that can be generated in accordance with the Brayton cycle is the total number of all 4 processes that occur in the cycle. The efficiency of a heat engine describes the work performance of the engine. The greater the efficiency value, the better the working performance of the machine. Based on the second law of thermodynamics which states related to the efficiency of a heat engine where the amount of heat energy that comes later from that energy will produce work which will later be used to carry out every process on the heat engine so that it becomes a cycle. During work, of course there is a waste of energy. The relationship between work efficiency, namely (Arifuddin & Mahardika, 2018) :

$$\eta = \frac{W}{Q_H} \quad (6)$$

where  $\eta$  is efficiency,  $W$  is action dan  $Q_H$  is the amount of incoming heat energy. From the relationship of these equations, to obtain maximum efficiency, of course, you must minimize waste energy and maximize the energy that goes into work. In this concept, in simple terms, the efficiency of the machine can be maximized.

The ratio between the volume of compressed air and the volume of energy wasted has a major effect on the combustion efficiency that occurs in a jet engine, causing a thrust. Where in a jet engine, the gas generator is the main power producer in a jet engine. Jet engine performance is influenced by several factors, namely jet fuel, electricity, hydrogen, aerodynamics, atmospheric conditions, altitude, temperature, humidity and weather. (Sukidjo, 2011). The efficiency of the machine is divided into 5, namely:

1. Thermal efficiency comes from an understanding of the ideal cycle which explains the ratio of energy in the form of work ( $W$ ) to energy in the form of incoming heat ( $Q_H$ ). where work ( $W$ ) is the result of reducing the incoming heat ( $Q_H$ ) with wasted heat energy ( $Q_c$ )
2. The thermal efficiency indicator is the thermal efficiency value of the actual cycle indicator diagram. The work of the indicator diagram is the work generated and the incoming heat energy is calculated based on the combustion process per kilogram.
3. Effective thermal efficiency is the ratio of shaft power or effective power to the heat input rate.
4. Mechanical efficiency is the ratio of shaft power and indicator power where the indicator works for each unit of time which will be converted into shaft work per unit time.

Of course, based on the thermodynamic concept, in order to maximize engine efficiency it is necessary to pay attention to several main factors that can move the aircraft, namely the amount of power generated and the weight of the engine. The heavier the machine, of course the greater the power required (Fahrizal, 2016). In terms of aircraft fuel usage, if the power used in the engine is very large, of course the fuel consumption is also large (Julianto & Sunaryo, 2020). In terms of the load that the aircraft can carry, the lighter the aircraft engine, the more cargo the aircraft can carry (Saroinsong et al., 2018). Currently, there have been many modifications to aircraft engines taking into account these factors (DAI et al., 2008; Guynn et al., 2011). For example, the T70 Turbocharger has a radial type of turbine that has an efficiency value of 60% which will be modified into a turbojet engine. To get a higher efficiency value on a turbojet engine. This single stage axial turbine is expected

to have an efficiency of 87% and can supply power to a compressor of 120,000 Watts (Hidayat, 2017). In addition, the hot core engine compartment of the turbojet engine is cooled by the rated flow of coolant air exhaled through the nacelle laminar flow system. This arrangement reduces the need to remove bypass ram air from the engine performance cycle for cooling purposes and thereby improves specific fuel consumption and engine efficiency. A turbocompressor pump driven by airflow from the core engine compressor draws cooling air through the laminar flow nacelle system and pumps air into the manifold surrounding the core engine (Miller, 1994).

Apart from improving the performance of the aircraft engine such as producing maximum power, fuel consumption and a slight reduction in engine weight, it is necessary to pay attention to external impacts that can be generated such as noise. Airplane noise has a serious impact on human health (Lumbantobing & Assisi, 2019). Significant advances are being made with noise reduction for turbofan engines. (Huff, 2007). Modifications were made to such as the LSU-02 unmanned aircraft developed by Pustek LAPAN with modifications to the length and width of the muffler on the 3W28i engine. the wider (larger diameter) of the muffler by approximately 80 mm contributes to a 21.587 dB reduction in sound levels. A modified muffler length with a diameter of 80 mm and a length of 130 mm can contribute to a noise reduction of 20.929dB (Sofia & Hakiki, 2020). Additionally the noise cancellation can be modified from the combination of the mixing nozzle and the ejector. After being tested tested on two full scale turbojet engines. Reduces the maximum sound pressure level by 12 dB and reduces the sound power level by 8 dB (Coles et al., 1958). Noise reduction can also be done at the junction plane between the air intake structure and the aircraft turbojet fan casing (Porte & Lalane, 2014).

#### 4. CONCLUSION

Based on the thermodynamic concept related to heat engines that apply the Brayton cycle, maximum efficiency can be done by reducing wasted heat energy and maximizing the work produced. From this concept, the desire to seek maximum engine efficiency results in many jet engine modifications by maximizing the function of the main factors of engine efficiency such as: Producing large power, low fuel consumption and striving for a light engine weight so that the aircraft's payload capacity is maximized. Current modification steps such as design changes that have a significant impact on the reduction of aircraft weight and

the design of the fuel limit with low fan pressure, high design bypass ratio will reduce aircraft noise levels.

## REFERENCES

- Arifuddin, M., & Mahardika, A. I. (2018). *Termodinamika*. Nas Media Pustaka.
- Aydin, H., Turan, Ö., Karakoç, T. H., & Midilli, A. (2013). Exergo-sustainability indicators of a turboprop aircraft for the phases of a flight. *Energy*, 58, 550–560.
- Coles, W. D., Mihalow, J. A., & Callaghan, E. E. (1958). *Turbojet engine noise reduction with mixing nozzle-ejector combinations* (Issue 4317). National Advisory Committee for Aeronautics.
- DAI, S., YU, J., & SUN, Y. (2008). Improved Design of a Small Turbojet Engine [J]. *Aeroengine*.
- Fahrizal, M. S. (2016). *Analisis Pertumbuhan Penggunaan Pesawat terhadap Beban Emisi Karbon Bandar Udara Internasional Juanda*. Institut Teknologi Sepuluh Nopember.
- Guynn, M. D., Berton, J. J., Fisher, K. L., Haller, W. J., Tong, M. T., & Thurman, D. R. (2011). *Refined exploration of turbofan design options for an advanced single-aisle transport*. NASA/TM-2011-216883.
- Haryanto, A. (2016). *Termodinamika*. Innosain.
- Hermawan, R., Prasetyo, E., & Pane, E. A. (2018). *Analisa Termodinamika Ruang Bakar Generator Set Berbahan Bakar Gas*. *Prosiding Semnastek 2018*, 1(1).
- Hidayat, Z. (2017). Perancangan Turbin Aksial Satu Tingkat Untuk Mesin Turbojet Berbasis Turbocharger T70. *Langit Biru: Jurnal Ilmiah Aviasi*, 10(3), 10–19.
- Huff, D. L. (2007). Noise reduction technologies for turbofan engines. *National Aeronautics and Space Administration*.
- Julianto, E., & Sunaryo, S. (2020). Analisis Pengaruh Putaran Mesin pada Efisiensi Bahan Bakar Mesin Diesel 2DG-FTV. *Jurnal Penelitian Dan Pengabdian Kepada Masyarakat UNSIQ*, 7(3), 225–231.
- Kusmayanti, H. (2016). Penerapan dan Permasalahan Eksekusi Pesawat Terbang Berdasarkan Hukum Acara Perdata Dalam Perjanjian Perawatan Mesin Pesawat. *Jurnal Bina Mulia Hukum*, 1(1), 26–35.
- Lumbantobing, S. S., & Assisi, F. (2019). Tingkat Kebisingan Suara di Lingkungan MTS Negeri 34 Jakarta terhadap Kualitas Proses Belajar Mengajar. *Jurnal EduMatSains*, 4(1), 51–64.

- Miller, F. E. (1994). *Turbojet cooling system*. Google Patents.
- Muku, I., & Sukadana, I. G. K. (2009). Pengaruh Rasio Kompresi terhadap Unjuk Kerja Mesin Empat Langkah Menggunakan Arak Bali sebagai Bahan Bakar. *Jurnal Ilmiah Teknik Mesin CakraM*, 3(1), 26–32.
- Keputusan Menteri Perhubungan Republik Indonesia Nomor KM 115 Tahun 2020, (2020). [http://jdih.dephub.go.id/assets/uudocs/kepmen/2020/KM\\_115\\_TAHUN\\_2020.pdf](http://jdih.dephub.go.id/assets/uudocs/kepmen/2020/KM_115_TAHUN_2020.pdf)
- Porte, A., & Lalane, J. (2014). *Noise reduction assembly for aircraft turbojet*. Google Patents.
- Priyono, E. (2020). Sekilas Tentang Pesawat. *Jurnal Industri Elektro Dan Penerbangan*, 1(1).
- Retnowati, N. D., Mulyani, S., & Talantha, F. (2019). Three Dimensional Simulation of Changes in Air Flow on a Jet Engine Desktop Based. *Compiler*, 8(1), 45–56.
- Rosyidin, A. (2017). Perbaikan, Dampak Korosi Pada Pesawat Udara Boeing 737. *Motor Bakar: Jurnal Teknik Mesin*, 1(1).
- Royce, R. (2015). *The jet engine*. John Wiley & Sons.
- Saroinsong, H. S., Poekoel, V. C., & Manembu, P. D. (2018). Rancang Bangun Wahana Pesawat Tanpa Awak (Fixed Wing) Berbasis Ardupilot. *Jurnal Teknik Elektro Dan Komputer*, 7(1), 73–84.
- Schwarz, F. M., & Gorbounov, M. B. (2014). *Thermal management system for turbofan engines*. Google Patents.
- Seldner, K. (1972). *Generalized simulation technique for turbojet engine system analysis*. National Aeronautics and Space Administration.
- Sofia, E., & Hakiki, I. A. (2020). Analisis Pengaruh Pemasangan Muffler pada Mesin Pesawat Tanpa Awak LSU 02 Terhadap Tingkat Kebisingan. *Infomatek: Jurnal Informatika Manajemen Dan Teknologi*, 22(2), 51–60.
- Sukidjo, F. X. (2011). Performa Mesin Sepeda Motor Empat Langkah Berbahan Bakar Premium dan Pertamina. *Forum Teknik*, 34(1).

# THERMODYNAMIC CONCEPTS ON EFFICIENCY

---

## ORIGINALITY REPORT

---

16%

SIMILARITY INDEX

14%

INTERNET SOURCES

9%

PUBLICATIONS

7%

STUDENT PAPERS

---

## PRIMARY SOURCES

---

1	<a href="http://www.devileye.net">www.devileye.net</a> Internet Source	2%
2	<a href="http://www.freepatentsonline.com">www.freepatentsonline.com</a> Internet Source	1%
3	B Setiawan, D Widiatmoko, I Siradjuddin, S Adhisuwignjo, F Ronilaya, M Syafaat. "Glidding system for a fixed wing aircraft using PID control algorithm", Journal of Physics: Conference Series, 2019 Publication	1%
4	<a href="http://ascelibrary.org">ascelibrary.org</a> Internet Source	1%
5	<a href="http://docplayer.info">docplayer.info</a> Internet Source	1%
6	Hazar Kusmayanti, Sandi Yusta Hawari. "PRAKTIK EKSEKUSI RIIL TANAH MILIK MASYARAKAT ADAT SUNDA WIWITAN", SASI, 2020 Publication	1%

---

7	Submitted to Monash University Student Paper	1%
8	"Exergy for A Better Environment and Improved Sustainability 1", Springer Science and Business Media LLC, 2018 Publication	1%
9	<a href="http://jdih.dephub.go.id">jdih.dephub.go.id</a> Internet Source	1%
10	<a href="http://repository.uki.ac.id">repository.uki.ac.id</a> Internet Source	1%
11	<a href="http://www.dtic.mil">www.dtic.mil</a> Internet Source	1%
12	<a href="http://repository.its.ac.id">repository.its.ac.id</a> Internet Source	1%
13	<a href="http://yudetandewi10.blogspot.com">yudetandewi10.blogspot.com</a> Internet Source	1%
14	<a href="http://sinta.ristekbrin.go.id">sinta.ristekbrin.go.id</a> Internet Source	1%
15	Submitted to Embry Riddle Aeronautical University Student Paper	1%
16	Submitted to Cranfield University Student Paper	<1%
17	<a href="http://sinta3.ristekdikti.go.id">sinta3.ristekdikti.go.id</a>	

---

Internet Source

<1%

---

18

[www.scilit.net](http://www.scilit.net)

Internet Source

<1%

---

19

[ejurnal.ubharajaya.ac.id](http://ejurnal.ubharajaya.ac.id)

Internet Source

<1%

---

20

Submitted to University of Warwick

Student Paper

<1%

---

21

[stpicurug.ac.id](http://stpicurug.ac.id)

Internet Source

<1%

---

22

[e-journal.staima-alhikam.ac.id](http://e-journal.staima-alhikam.ac.id)

Internet Source

<1%

---

23

[mdao.grc.nasa.gov](http://mdao.grc.nasa.gov)

Internet Source

<1%

---

24

Sadraey, . "Propulsion System Design", Aircraft Design A Systems Engineering Approach, 2012.

Publication

<1%

---

25

Meinhard T. Schobeiri. "Gas Turbine Design, Components and System Design Integration", Springer Science and Business Media LLC, 2019

Publication

<1%

---

Exclude quotes      On

Exclude matches      Off

Exclude bibliography      Off